EZ50 Pull line blower
for the electrical installer



Standard equipment in strong plastic case
current source 230V/10A or 115V/20A



The simple way to

blow or

vacuum pull line.

Facts

- **Blow** or **vacuum** pull line **without compressor** (ø 1 mm, tensile strength 24 kg)
- For commercially available cable conduits (inner pipe diameter from 18 to 50 mm / ¾" to 2")
- Suitable for **flexible pipes**
- For installations in residential, commercial and industrial building
- **Trouble shooter** for blocked conduits
- Huge **time saving** in cable feeding on longer distances
- **Several hundred meters** of cord pulling possible
- Lightweight and compact
- Easy to handle
- Excellent accessibility, even in confined spaces
- Suitable in any car boot
- Excellent price/performance ratio





See Video EZ50

Zeitler AG
Sonnhalde 7
CH-6206 Neuenkirch
Switzerland

Tel. +41 (0)41 467 16 14
Mail: info@zeitler.swiss
Web: www.zeitler.swiss

SWISS MADE

EZ50 Pull line blower
for the electrical installer

Intended Use:

- insert a special pull line in all commercial conduits with ID from **ø 18 to 50 mm / ¾" to 2"**
- for electrical cable installations in private, business and industrial buildings
- for all commercial boxes, junction boxes, sockets, lamp boxes etc. (even in very confined spaces)
- problems with e.g. kinked conduits can be solved by switching to suction mode, sucking the pull line from opposite end

Technical Data:

- Electrical Data: according to local specification (230V/50 Hz o 115V/60Hz)
- Minimum unit power: 2000 W
- Thermal circuit breaker
- Degree of protection: IP 20
- Maximum air flow rate: Blowing/suction 4 m³/min
- Weight: 4 kg
- Dimension (unit only): 443 mm x 252 mm (length x width)



Scope of supply EZ50 Pull line blower with STANDARD Equipment

in strong plastic case

- 1 EZ50 Pull line blower
- 2 Pull line rolls ø 1 mm, approx. 900 m, tensile strength approx. 24 kg
- 1 Suction device
- 1 Components set A: for conduits with an internal ø 18 - 20 mm
- 1 Components set B: for conduits with an internal ø 20 - 26 mm
- 1 Components set C with bend: for conduits and wall boxes with an internal Ø 18 - 20 mm
- 1 Special nozzle black, for internal diameter from 25 to 50 mm
- 3 Beads of ø 11, 13 and 16 mm each
- 1 Instruction manual

Also available as **EZ50 +PLUS Equipment** including following extra accessories



- 1 Shuttle set - dimension free of choice from ø 20-50 mm / ¾" - 2" for cleaning, taking water out and calibrating the conduits



- 1 Parachute for ducts ø 30-60 mm / 1" bis 2 ½"
- 1 Pull line roll ø 1 mm, approx. 900 m, tensile strength approx. 24 kg
- 1 Box with Shuttle assembly material

Zeitler AG
Sonnhalde 7
CH-6206 Neuenkirch
Switzerland

Tel. +41 (0)41 467 16 14
Mail: info@zeitler.swiss
Web: www.zeitler.swiss

EZ50 Pull line blower for the electrical installer

Special accessories (to be ordered separately):

- Special nozzle with 90° angle (external diameter 12 mm)
  to simplify blowing cord into light socket boxes



- Spray nozzle for lubricants



- Beats round ø 11 mm (PU 5 pieces) (Art. N° 100040)
- Beats round ø 13 mm (PU 5 pieces) (Art. N° 100041)
- Beats round ø 16 mm (PU 5 pieces) (Art. N° 100042)



- Beats long ø 11 mm (PU 2 pieces) (Art. N° 100043)
- Beats long ø 13 mm (PU 2 pieces) (Art. N° 100044)
- Beats long ø 17 mm (PU 2 pieces) (Art. N° 100316)



- Lubriball 22 mm
  Sponge ball for cleaning or lubricating ø 12-20 mm ducts
  (PU 10 pieces) (Art. N° 100330)



Suitable Pull Line:

- Cable Pull Line ø 1 mm, tensile strength 24 kg
  1 box with 10 rolls of ca. 900 m (Art. N° 100132)



See more
EZ50 accessories

Zeitler AG
Sonnhalde 7
CH-6206 Neuenkirch
Switzerland

Tel. +41 (0)41 467 16 14
Mail: info@zeitler.swiss
Web: www.zeitler.swiss

SWISS MADE