AC clamp meters

PAN 200A+

Smart clamp meter 200 A AC CAT III 600 V with automatic function selection and non-contact voltage detection

- Digital display 13 mm
- **Display backlight**
- **1-stage contactless voltage testing (NCV)**
- **Single-pole phase test with acoustic alarm**
- Automatic range selection
- Data hold
- **Resolution 1 mA**
- Automatic switch-off

Scope of delivery: Case, Test leads, Operating instructions



Application Benefits at a Glance:

- At just 15.9 cm long, it is exceptionally handy for tight and densely populated distribution boards.
- Current is measured without disconnecting the conductor; automatic function selection reduces operation to just a few steps.
- The fine 1 mA resolution also reveals smaller changes in AC current.

Technical Data	PAN 200A+
DC voltage DC (V =)	0,1 V - 600 V
AC voltage AC (V ~)	0,1 V - 600 V
AC current AC (A ~)	1 mA - 200 A
Resistance (Ω)	1 Ω - 6 kΩ
Audible continuity tester •)))	< 50 Ω
Frequency (Hz)	40 Hz - 1000 Hz
Clamp opening ⌀	20 mm
Weight (gross / net)	316 / 122 g
Instrument dimensions	159 x 60 x 29 mm
Required battery(ies):	2 x 1,5 V AAA
Measurement category (CAT)	CAT III 600 V
Accuracy (%)	0,5 % - 2,5 %





PAN 200A+ Video DE:

PAN 200A+ Video EN: