Compact digital multimeters True RMS

PAN Minimeter-2

Digital multimeter True RMS CAT III 600 V with manual range selection and non-contact voltage detection

- **Backlit digital display with analogue bargraph 22 mm**
- **3-stage contactless voltage testing (NCV)**
- Polarity indication for DC voltage
- **True RMS measurement**
- Digital display 22 mm
- **Single-pole phase test with acoustic alarm**
- Data hold
- Diode test
- **LED torch**
- Automatic switch-off

Scope of delivery: Test leads, Operating instructions



Application Benefits at a Glance:

- One test lead can be secured at the rear, allowing the device to be held in one hand and guided directly to the measurement point.
- The analogue bar graph shows fluctuations and changes faster than a purely numeric display.
- Well suited to troubleshooting in domestic installations, appliances and electronic power supplies.

Technical Data	PAN Minimeter-2
DC voltage DC (V =)	0,1 mV - 600 V
AC voltage AC (V ~)	10 mV - 600 V
DC current DC (A =)	0,1 µA - 10 A
Resistance (Ω)	0,1 Ω - 4 MΩ
Audible continuity tester •)))	< 50 Ω
Instrument dimensions	166 x 78 x 48 mm
Weight (gross / net)	382 / 252 g
Required battery(ies):	2x 1,5 V AAA
Measurement category (CAT)	CAT III 600 V
Accuracy (%)	0,8 % - 3 %





PAN Minimeter-2 Video DE:

PAN Minimeter-2 Video EN: